Rely on us.[®]



rotec[®] Label Sleeve

Hard sleeve with high dimension stability, specially developed for narrow web machines

Available wall thicknesses from 10 mm to 125 mm Special sizes available on request

Product advantages

- Constant parallelism of the sleeve in printing with optimum edge-stability for excellent results in label printing
- Consistent printing properties through high dimension stability
- Long-lasting and continuous register accuracy

Product features

- Extremely durable polyurethane surface (75 Shore D)

 generally scratch and solvent resistant if handled correctly (see rotec[®] User's Advice)
- Proven rotec[®] interior design of synthetic resin and fibre compound assures long-lasting and consistent mounting characteristics
- Suitable for all plate and adhesive tape thicknesses
- Can be combined with various types of adapters

- Constant outer diameter at fluctuating temperatures or high air humidity
- Simple adhesive tape dismounting
- Easy to handle due to low weight
- High-precision grinding (TIR ≤ 0.025 mm) measured on carrier cylinder at TIR ≤ 0.005 mm
- Tolerance of face-length according to DIN ISO 2768 T1 c



You are welcome to contact us for further information.

Flint Group Flexographic Products Solmsstraße 83 48683 Ahaus Germany T +49 711 9816-541 F +49 711 9816-801 info.flexo@flintgrp.com www.flintgrp.com All information in this document is based on our present knowledge and experience at the time of printing. Due to the multitude of factors influencing the processing and application of our products, it does not exempt the user from testing and calibrating. Nor does it imply any legally binding assurance concerning specific properties of the products or the suitability for a particular application. The responsibility of observing any possible industrial property rights, laws and regulations is the obligation of the user. Subject to technical changes without prior notice. Product names marked ® are registered trademarks of Flint Group.